

Uniden®

PRO•SERIES

Professional 4K Tamper Proof Dome Camera • 4KTPD-MVF



RJ45

4K
Recording

Moto
Varifocal

100FT
Night Vision

Intelligent Detection



Technology you trust for the highest quality security.

uniden.com

Camera Specifications

Camera

Sensor: 1/2.5" 8MP progressive scan CMOS

Min. Illumination: 0Lux/F1.4 (IR on) color: 0.1Lux/F1.4, B/W: 0.5Lux/F1.4

IR Distance: 100' Night Vision (12*IR LEDs)

Electronic Shutter: Auto/Manual (1/25-1/10000), FLK

Day & Night: ICR switch, auto, color, B/W, ext

Lens: 3.0-10mm motorized lens

Lens Interface: M14

Output: PAL/NTSC adjustable

WDR: Off/Low/Middle/High

Light Board Control: Auto/Manual/Off

3D N/R: Off/Low/Middle/High/Higher

Defog: Off/Low/Middle/High

Mirror: Off/Horizontal/Vertical/180° rotation/Corridor mode (90° rotation, 270° rotation)

Slow Shutter: Off/On

Exposure Control: Auto/Manual

Image Setting: Brightness, Contrast, Saturation, Sharpness, Hue

Audio/Video Encoding

Video Compression: H.265/H.264/MJPEG

H.265 Encoding: Main Profile

H.264 Encoding: BaseLine/Main Profile/High Profile

Encoding Features:

- NTSC
- Main stream: 3840*2160@30fps, Sub-stream: D1@30fps
- PAL
- Main stream: 3840*2160@25fps, Sub-stream: D1@25fps
- Max. Resolution: 3840x2160
- Video Bit Rate: Constant bit rate, variable bit rate (32Kbps-16Mbps)
- Video Type: Complex stream/Video stream
- Audio Compression: G.711u
- Audio Bit Rate: 64Kbps
- Audio Control: Support input/output volume gain control
- ROI: Support 4 zones, multi-stage level

Network

Network Protocol: TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP, FTP

Access Protocol: ONVIF

Browser: IE, Chrome, Firefox, Safari

OSD: Title, time and date overlay, multi-line OSD, OSD color optional

DST: Supported

Snapshot: Support snapshot, snapshot resolution is encoding resolution

System Update: Remote Update supported

Intelligent Detection: Target counting, left/lost, area detection, line crossing detection, scene change, motion detection, video loss, video tampering

Camera Interface

Network Interface: RJ45 10M/100M network adaptive

Power Jack: 2.1mm Power Jack for optional 12VDC input

Audio: Line input/output

Alarm Input: 2CH

Alarm Output: 1CH

Reset: Supported

RS485: Supported

Micro SD Card: Max 128GB, Micro SD (SDHC/SDXC) card local-storage

Camera General

Operating Temperature: -4°F-131°F

Operating Humidity: 0% - 90%

Protection Grade: IP66/IK10

Power Supply: PoE/12VDC (optional)

Power Consumption (max): <9W

Dimensions (in.): 4.61(L) * 4.61(W) * 3.39(H)



FREE Uniden Pro Wired App

Full Mobile remote control and setup from iPhone®, iPad®, iPod touch® and Android™ devices. Receive alerts via Email or Notification.

SYSTEM REQUIREMENTS: Router with Internet access and available Ethernet Port, iPhone®, iPad®, iPod touch® or Android™ device.

PACKAGE INCLUDES: (1) Tamper Proof Dome Indoor/Outdoor Camera, (1) Camera Mounting Hardware

©2017 Uniden America Corp., Irving TX. All rights reserved. Photography and illustrations may differ slightly from actual product. iPad®, iPhone® and iPod touch® are registered trademarks of Apple Inc. Android is a trademark of Google Inc. Amazon, Kindle, Fire and all related logos are trademarks of Amazon.com, Inc. or its affiliates. May contain additional foreign articles. Custom manufactured in China.

Proposition 65 Warning (California): This product contains a chemical known to The State of California to cause cancer, birth defect or other reproductive harm.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

UPC: 0 5063340735 6