

# Uniden®

## PRO·SERIES

Professional 2MP Varifocal Bullet Camera • 2MB-VF



RJ45

**2MP**  
MegaPixel

**1080p**  
Full HD

**Varifocal**  
Lens

**150FT**  
Night Vision



Control remotely from your  
smartphone or tablet.

Technology you trust for the highest quality security.

[uniden.com](http://uniden.com)

### Camera Specifications

#### Camera

Lens: 2.8-12mm varifocal lens  
Lens Interface: M14  
Image Sensor: 1/2.9" SONY 2.07 MP Progressive scan Exmor CMOS  
Day/ Night: ICR switch, auto, color, B/W, ext  
Effective Pixels: 2MP  
Min. Illumination: 0Lux/F1.4 (IR ON) Color: 0.06Lux/F1.4, B/W: 0.01Lux/F1.4  
IR Distance: 130-165' Night Vision 3xIR-III LEDs)  
Electronic shutter: Auto/Manual(1/25-1/10000), FLK  
R/N ratio: ≥50db (AGC OFF)  
Auto Iris: DC driver  
Output : PAL/NTSC adjustable  
WDR: DWDR (Off/Low/Middle/High)  
Light Board Control: Auto/Manual/Off  
3D N/R: Off/Low/Middle/High/Higher  
Defog: Off/Low/Middle/High  
Mirror: Off/Horizontal/Vertical/180° rotation/Corridor mode (90° rotation, 270° rotation)  
Slow Shutter: Off/On  
Exposure Control: Auto/Manual  
Image Setting: Brightness, Contrast, Saturation, Sharpness, Hue

#### Audio/Video Encoding

Video Compression: H.265/H.264/MJPEG  
H.265 Encoding: Main Profile  
H.264 Encoding: BaseLine/Main Profile/High Profile  
Encoding Features:  
NTSC:  
Main stream: 1920x1080@30fps,  
Sub-stream: D1@30fps  
PAL:  
Main stream: 1920x1080@25fps,  
Sub-stream: D1@25fps  
Max. Image Resolution: 1920x1080  
Video Bit Rate: Constant bit rate, variable bit rate (16kbps~8000kbps)  
Video Type: Complex stream/Video stream  
ROI: Support 4 zones,multi-stage level

#### Network

Network Protocol: TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP  
Access Protocol: ONVIF  
Browser: IE, Chrome, Firefox, Safari  
OSD: Title, time and date overlay, multi-line OSD  
DST: Supported  
Snapshot: Support snapshot, snapshot resolution is encoding resolution  
System Update: Remote Update supported

#### Camera Interface

Network Interface: RJ45  
10M/100M network adaptive  
Analog Video Output: 1CH 1.0Vp-p complex video output

#### Camera General

Operating Temperature: -4°F~131°F  
Operating Humidity: 0%-90%  
Protection Grade: IP66  
Power Consumption (max): <9W  
Power Supply: PoE with optional 12V  
Dimensions (in.): 10.35(L)\* 3.66(W)\* 3.76(H)



#### FREE Uniden Pro Wired App

Full Mobile remote control and setup from iPhone®, iPad®, iPod touch® and Android™ devices. Receive alerts via Email or Notification.

SYSTEM REQUIREMENTS: Router with Internet access and available Ethernet Port, iPhone®, iPad®, iPod touch® or Android™ device.

#### PACKAGE INCLUDES: (1) Varifocal Bullet Indoor/Outdoor Camera, (1) Camera Mounting Hardware

©2017 Uniden America Corp., Irving TX. All rights reserved. Photography and illustrations may differ slightly from actual product. iPad®, iPhone® and iPod touch® are registered trademarks of Apple Inc. Android is a trademark of Google Inc. Amazon, Kindle, Fire and all related logos are trademarks of Amazon.com, Inc. or its affiliates. May contain additional foreign articles. Custom manufactured in China.

Proposition 65 Warning (California): This product contains a chemical known to The State of California to cause cancer, birth defect or other reproductive harm.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

UPC: 0 5063340727 1