

PRO-SERIES

Professional Video Security XVR System • Pro1600X2





XVR Specifications

Video

Five-in-One Input: 1080p AHD, TVI, CVI, IP and 1280H analog Video Standard: PAL: NTSC

Video Compression: H.264

Video Resolution:

4MP/3MP/1080p/960p/720p/D1/4 CIF/DCIF/2CIF/CIF/QCIF

Video Input:

16CH*3MP(BNC)/4 main Play

8CH*4MP(BNC1,3,5,7,9,11,13,15)/4

main Play

16CH*3MP(BNC)+16CH*3MP(IPC) 16 Sub-Play/ 1 main Play

8CH*4MP (BNC1,3,5,7,9,11,13,15)

+8CH*4MP(IPC)

8 Sub-Play/1 main Play

Video Output: VGA/HDMI sync output: 1920×1080p@60Hz,

1440×900p@60Hz, 1366×768p@60Hz, 1280×1024p@60Hz, 1024×768p@60Hz, 800×600p@60Hz

Bit Rate: Self-Define (16-8000Kbps)

Image Display:

1/4/6/8/9/16/20/25/36

Snapshot: Support (JPEG)

Motion Detection: 396 (22*18) Surveyed area can be set in every screen and multi-level sensitivity

adjustable

Audio

Audio Encoding G.711u Audio Input: 4CH, RCA port Audio Output: 1CH, RCA port

Video Recording and **Playback**

Video Frame Rate: 8CH mode: 4MP@15fps:

3MP@10fps 1080p@25fps (PAL)/

30fps (NTSC) real-time;

720p@25fps(PAL)/30fps (NTSC)

real-time;

Analog/IPC@25fps(PAL)/30fps

(NTSC) real-time.

16CH mode: 3MP@15fps: 1080p@15fps; 720P@25fps (PAL)/30fps (NTSC) real-time; Analog/IPC@25fps(PAL)/30fps (NTSC) real-time.

Record Mode: Manual/Timing MD/Alarm exception/MD or alarm/MD and alarm

Playback Synchronic: Analog 4CH/hybrid 1CH sync-playback(Main stream) 8CH/16CH sync-playback (Sub stream)

Search Method: Time, Calendar, Event, Channel

Video Playback: Start, Stop, Fast play, Slow play, Frame play, Snapshot, Full screen, Roller amplification time ball precise playback

Storage Backup

Interface: 2 SATA

HDD Capacity: Single largest 6TB

Backup location: Local HDD,

Network

Backup Method: Network, USB

storage device

Function

Network Protocol: TCP/IP, HTTP, DDNS, SMTP(SSL), DHCP, PPPoE, UPNP, NTP, P2P, ONVIF

Interface Protocol: ONVIF, RTSP

Mobile Surveillance: Apple,

Android

Browser: IE, Chrome, Firefox, Safari

Intelligent Detection: Motion detection/video loss/video

tampering

External Interface

Video Input: 16CH BNC port $(1.0 \text{Vp-p}, 75\Omega)$

Network Interface: 1RJ45

10M/100M self-adaptive Ethernet

port

Alarm Input: 8CH Alarm Output: 3CH

RS485 Interface: 1RS485 port

USB Port: 2 USB2.0

XVR General

Power Supply: 12VDC/5A Power Consumption: 35W (Without HDD)

Operating Temperature: -4°F~131°F Operating Humidity: 10%-90%

Dimensions (in.):

14.17 (L)* 10.31(W)* 1.91(H)

Weight: 3 lb 5 oz







FREE Uniden Pro Wired App

Full Mobile remote control and setup from iPhone®, iPad®, iPod touch® and Android™ devices. Receive alerts via Email or Notification. SYSTEM REQUIREMENTS: Router with Internet access and available Ethernet Port, iPhone®, iPad®, iPod touch® or Android™ device.

PACKAGE INCLUDES: (1) 16 Channel Full HD XVR, (1) 12V Power Adapter for XVR, (1) USB Mouse and Quick Start Guide

©2017 Uniden America Corp., Irving TX. All rights reserved. Photography and illustrations may differ slightly from actual product, iPad", iPhone" and iPod touch "are registered trademarks of Apple Inc. Android is a trademark of Google Inc. Amazon, Kindle, Fire and all related logos are trademarks of Amazon.com, Inc. or its affiliates. May contain additional foreign articles. Custom manufactured in China.

Proposition 65 Warning (California): This product contains a chemical known to The State of California to cause cancer, birth defect or other reproductive harm.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.